

## CMC DYNAMIC I-LANYARDS



Versatile and efficient, CMC's Dynamic I-Lanyards are excellent multipurpose tools for high angle rope work and essential kit for the technical professional. Ideal for rope access, arbor, rescue, and via ferrata. Dynamic I-Lanyards come in 24" (61 cm) and 30" (76 cm) sizes, offering a variety of attachment options and technical uses. They are designed to reach specified length when a 10 kg load is applied in accordance with EN 354 and have a +/- 1" (2.54 cm) tolerance.

Dynamic I-Lanyards are made from 11 mm dynamic Teufelberger Apex rope with a dry treated core. This rope was selected for supple handling and high durability, making lanyards easy to manipulate and load into devices like a chest ascender. I-Lanyards are assembled using relaxed rope to minimize variations, twists, and shrinking over time. They are 100% inspected and every lot is sampled and strength tested for validation. Made in the USA with automated sewing for a repeatable and reliable stitch pattern,

CMC's I-Lanyards are certified as Lanyards according to EN 354: 2020 and Temporary Anchor Devices according to EN 795/B: 2012. They function as both fall arrest PPE as well as anchor devices when wrapped around structures in basket configuration. Sewn terminations at each end include thimbles to maintain loop integrity and prevent cross-loading. CMC's I-Lanyards come with large thimbles installed at each eye, sized for compatibility with connectors. A small thimble is also included, sized for compatibility with quick-links. Thimbles are removable and can be swapped in or out.

### Features:

- Multi-purpose tool and PPE for rope access, arbor, rescue, and via ferrata
- Key element for working on rope and vertical progression, including:
  - Work positioning
  - Fall arrest
  - Aid climbing
  - Passing a deviation
  - Connecting to anchors
  - Attaching to highlines
  - Leashing equipment
  - Rescues & pick-offs
- Certified as lanyards under fall arrest standard and as temporary anchor devices

- Two sizes allow variety of uses when connected to sternal or ventral D-Ring
- Sewn terminations with thimbles for maintaining loop integrity and connector position
- Comes with 2 large thimbles installed and 1 additional small thimble included
- Constructed from relaxed rope, 100% inspected, and strength tested in each lot
- Dynamic I-Lanyards are 11 mm Teufelberger Apex rope with dry treated core
- Sized to reach specified length when 10 kg of load is applied, +/- 1" tolerance
- Made in the USA

## Certifications

- Lanyards according to EN 354: 2020
- Temporary Anchor Devices according to EN 795/B: 2012

[Click here for the CMC Bullnose & I-Lanyards PPE Procedures & Resources.](#)

Option	Dynamic I-Lanyard 24"
Item	201851
MATERIAL	TEUFELBERGER APEX (DYNAMIC)
COLOR	PURPLE HAZE
DIAMETER	11 MM (7/16)
WEIGHT	86 G (.19 LB)
LENGTH	24 IN (61 CM)
CERTIFICATION	EN 354: 2020; EN 795/B: 2012
MBS	22 KN (4946 LBF)
Option	Dynamic I-Lanyard 30"
Item	201852
MATERIAL	TEUFELBERGER APEX (DYNAMIC)
COLOR	GREEN SPRING
DIAMETER	11 MM (7/16)
WEIGHT	100 G (.22 LB)
LENGTH	30 IN (76 CM)
CERTIFICATION	EN 354: 2020; EN 795/B: 2012
MBS	22 KN (4946 LBF)
Option	Thimble, Small
Item	P12995
MATERIAL	POLYPROPYLENE
COLOR	BLACK

<b>DIAMETER</b>	ACCEPTS UP TO 10 MM (0.39 IN) DIAMETER CONNECTOR
<b>WEIGHT</b>	N/A
<b>LENGTH</b>	N/A
<b>CERTIFICATION</b>	N/A
<b>MBS</b>	N/A

---

<b>Option</b>	Thimble, Large
<b>Item</b>	P12591
<b>MATERIAL</b>	POLYPROPYLENE
<b>COLOR</b>	BLACK
<b>DIAMETER</b>	ACCEPTS UP TO 14 MM (0.55 IN) DIAMETER CONNECTOR
<b>WEIGHT</b>	N/A
<b>LENGTH</b>	N/A
<b>CERTIFICATION</b>	N/A
<b>MBS</b>	N/A

---

1-800-235-5741

[info@cmcpro.com](mailto:info@cmcpro.com)

[cmcpro.com](http://cmcpro.com)