

## PRUSIK CORD & LOAD RELEASE HITCH CORD





The most important attributes of a cord used for Prusik hitches are consistency in handling, diameter and strength. Once you have determined the Prusik hitch that works best on your host rope, you want the same performance every time you replace it. CMC Prusik Cord has the right balance of suppleness for reliable activation, but is not so soft that it wears out rapidly. Made of 100% nylon with a torque-free, kernmantle construction, it comes in solid colors to help differentiate between cords designed for Prusik hitches and climber's accessory cords. Two color choices allow you to use a separate color for each length Prusik in a Tandem Prusik Belay System. The 9-mm cord is the size preferred by rescuers who use cord for a Load-Releasing Hitch.

Cord is sold by the foot. Please see the table below for maximum lengths available for order.

Certain products on this page have clearance pricing and are not able to be returned or exchanged.

Option	6 MM - ORANGE W/ BLUE STRIPE CUSTOM LENGTH
Item	293011
WEIGHT PER FOOT	8.5 G (0.3 OZ)
COLOR	ORANGE / BLUE
MBS	8 KN (1,798 LBF)
MAX LENGTH	183 M (600 FT)
Option	6 MM - BLUE W/ ORANGE STRIPE CUSTOM LENGTH
Item	293012
WEIGHT PER FOOT	8.5 G (0.3 OZ)

COLOR	BLUE / ORANGE
MBS	8 KN (1,798 LBF)
MAX LENGTH	183 M (600 FT)
Option	7 MM - YELLOW CUSTOM LENGTH
Item	293017
WEIGHT PER FOOT	8.5 G (0.3 OZ)
COLOR	YELLOW
MBS	8 KN (1,798 LBF)
MAX LENGTH	549 M (1,800 FT)
Option	7 MM - BLUE CUSTOM LENGTH
Item	293037
WEIGHT PER FOOT	8.5 G (0.3 OZ)
COLOR	BLUE
MBS	8 KN (1,798 LBF)
MAX LENGTH	549 M (1,800 FT)
Option	8 MM - GREEN CUSTOM LENGTH
Item	293018
WEIGHT PER FOOT	14 G (0.5 OZ)
COLOR	GREEN
MBS	14 KN (3,147 LBF)
MAX LENGTH	366 M (1,200 FT)
Option	8 MM - RED CUSTOM LENGTH
Item	293038
WEIGHT PER FOOT	14 G (0.5 OZ)
COLOR	RED
MBS	14 KN (3,147 LBF)
MAX LENGTH	366 M (1,200 FT)
Option	9 MM - ORANGE CUSTOM LENGTH
Item	293039
WEIGHT PER FOOT	17 G (0.6 OZ)
COLOR	ORANGE

**MBS** 15 KN (3,372 LBF)

**MAX LENGTH** 366 M (1,200 FT)

1-800-235-5741 info@cmcpro.com cmcpro.com